



Možnosti montáže topných přírubových jednotek řady TPK

Průměr nádoby [mm]	Typ	TPK 150-8/ 2,2 kW	TPK 168-8/ 2,2 kW	TPK 210-12/ 2,2 kW	TPK 210-12/ 3-6 kW	TPK 210-12/ 6,6 kW	TPK 210-12/ 5-9 kW	TPK 210-12/ 8-12 kW
500	OKCE 160 S	-	-	▲	▲	▲	-	-
	OKC 160 NTR/BP	-	▲	-	-	-	-	-
	OKCE 200 S	-	-	▲	▲	▲	-	-
	OKC 200 NTR/BP	-	▲	-	-	-	-	-
	OKC 200 NTRR/BP	-	▲	-	-	-	-	-
	OKCE 250 S	-	-	▲	▲	▲	-	-
	OKC 250 NTR/BP	-	▲	-	-	-	-	-
	OKC 250 NTRR/BP	-	▲	-	-	-	-	-
550	OKCE 300 S	-	-	▲	▲	▲	▲	▲
	OKC 300 NTR/BP	-	-	▲	▲	▲	-	-
	OKC 300 NTRR/BP	-	-	▲	▲	▲	-	-
	OKC 300 NTR/HP	▲	-	-	-	-	-	-
	OKCE 400 S	-	-	▲	▲	▲	▲	▲
	OKC 400 NTR/BP	-	-	▲	▲	▲	-	-
	OKC 400 NTRR/BP	-	-	▲	▲	▲	-	-
	OKC 400 NTR/HP	▲	-	-	-	-	-	-
600	OKC 400 NTRR/HP/SOL	▲	-	-	-	-	-	-
	OKCE 500 S	-	-	▲	▲	▲	▲	▲
	OKC 500 NTR/BP	-	-	▲	▲	▲	-	-
	OKC 500 NTRR/BP	-	-	▲	▲	▲	-	-
	OKC 500 NTR/HP	▲	-	-	-	-	-	-
	OKC 500 NTRR/HP/SOL	▲	-	-	-	-	-	-
	OKCE 750 S	-	-	■	■	■	■	■
	OKC 750 NTR/BP	-	-	■	■	■	■	■
850	OKCE 1000 S	-	-	■	■	■	■	■
	OKC 1000 NTR/BP	-	-	■	■	■	■	■
	OKC 1000 NTRR/BP	-	-	■	■	■	■	■

- ▲ lze montovat
- lze montovat jen s redukční přírubou 225/210
- nelze montovat